

# MORTERO SECO Gris

Grey dry mortar



## What is this product

- It's a grey mortar ready to use mixed with water.
- Principal applications are given in little domestic use works for brick laying, walls, floors, etc...

## Characteristics

- Easy application
- Do-it-yourself indicated product
- Great commodity (cement and sand already mixed)
- Great adherence power for aislant elements fixing
- Monocomponent (Just add water)



## How to prepare

- 1- The mixing is traditional, like every mortar.
- 2- Add the water it needs, in user's convenience until getting a strong and consistent paste (usually 4 litres per each 25 kgs)

## Where to use

Ceramic material fixing, for interiors and exteriors

**Using substrates:** Cement floors and walls, cement-lime mortar brick. Substrates must be solid, clean, dry and without deformations.

**Do not use:** On metal, fiber-cement, wood and old tiles.

For these applications, mix PANZER with ADESILATEX.

On concrete, mix MORTERO SECO with ADESILATEX.

## Technical Data: Mortero Seco Gris

Aspect	Grey Powder
Presentation	25 kgs bag
Resistance to compresion after 28 days	M 10
Reaction to fire	A1
Mixing water	4 litres each 25 kgs
Chloride	less 0,01%
Water absortion	0,43 kg/m2 min0,5
Open time	1,45 hours
Temperature during application	min 3°C, max 30°C
Thermal resistance	-5°C to 80°C
Bulk density	1,6 gr/cm3
Stockage (from manufacturing date, under cover, in a dry place)	12 months



## Composition

- Grey cement
- Siliceous soils

## Precautions

Product components are not toxic.  
It must be worked with gloves, avoid powder inhalation and contact with eyes and skin.  
Keep away from children or animals.

## First Aid

Skin: Wash with plenty of water  
Eyes: Wash with plenty of water  
Ingestion: Rinse with water and drink plenty of water

This technical data is written according to our knowledge and essays and doesn't assume any commitment. It's on customer's responsibility the admission and control in the distributor's warehouse or construction, as well as the election of the product to be used on each case. Manufacturer's responsibility is limited to manufacturing defects and for the value of the merchandise because it's out of his control the material election and the working conditions. Technical data for 2018.



Headquarters: Camino Viejo de Simancas, Km. 4 - 47008 Valladolid (Spain) / telf: +34 983 47 52 12  
papresa@papresa.net - www.papresa.net