

# MORTERO SECO DE PROYECCIÓN

Dry mortar for mechanical application



## What is this product

- It's a grey mortar to be projected with machine on brick walls or concrete blocks, acting as a glue for the fiberglass boards or rockwool rolls.

Also for cement walls.



## Characteristics

- Easy application with projection machinery.
- Great adherence power for aislant elements placing.
- Waterproof: Protects against humidity.
- Monocomponent.

## How to prepare

- 1- This product is specially designed to be applicated with projection machinery
- 2- It's recommended to adjust the machine in a 25% mortar/water relation and modify this relation until getting the paste density wanted. The mortar/water relation may change depending on working conditions.
- 3- In case of hand application, mix in a 6-7 water litres bowl per each 25 mortar kgs.

## How to use

- Project the mortar on the wall. The water volume must be graduated to get a paste density with no slipping-off.
- Once projected, mortar must be smoothed with a trowel, trying that all the surface is covered and eliminating at once, possible air bags.
- Resultant coat width must be between 5 and 8 mm.
- Fix the fiberglass or rockwool panels through manual pression. It's recommended to place these aislant panels from up to down, for the panels that must be cutted are the ones down, in order to ease the work as much as possible.
- Fix the panels during the "open time" (20 minutes). Out of this time, properties are reduced.

## Technical Data: Mortero Seco de Proyección

Aspect	Grey Powder
Presentation	25 kgs bag
Output	6-7 kg/m <sup>2</sup>
Mixing water	+/- 25%
Coat width	5-10 mm
Open time	20 minutes
Temperature during application	min 3°C, max 30°C
Reaction to fire	A1
Stockage (from manufacturing date, under cover, in a dry place)	12 months



## Composition

- Grey cement
- Siliceous soils
- Additives

## Precautions

Product components are not toxic.  
It must be worked with gloves, avoid powder inhalation and contact with eyes and skin.  
Keep away from children or animals.

## First Aid

Skin: Wash with plenty of water  
Eyes: Wash with plenty of water  
Ingestion: Rinse with water and drink plenty of water

This technical data is written according to our knowledge and essays and doesn't assume any commitment. It's on customer's responsibility the admission and control in the distributor's warehouse or construction, as well as the election of the product to be used on each case. Manufacturer's responsibility is limited to manufacturing defects and for the value of the merchandise because it's out of his control the material election and the working conditions. Technical data for 2018.



Headquarters: Camino Viejo de Simancas, Km. 4 - 47008 Valladolid (Spain) / telf: +34 983 47 52 12  
papresa@papresa.net - www.papresa.net