

YESO CONTROLADO

Retarded gypsum



What is this product

- It's a thick construction gypsum for handy application and slow forging, for interior wall covering works.

Most common uses:

- Filling of wall-roof meetings
- Filling of doors and windows pre-frames
- Wireway covering
- Electric box fixing
- Indoor walls



Characteristics

- Easy application by hand
- Retarded
- Minimum retraction after forging
- Monocomponent

How to prepare

- 1- Sprinkle the gypsum over the water
- 2- Mix with a mixer machine until getting a creamy paste.
- 3- Let it settle during some minutes
- 4- Apply handly with a trowel or a spatula.

Technical Data: Yeso Controlado

Aspect	White Powder
Presentation	20 kgs bag
Water / gypsum relation	0,8
Forging start	16-18 minutes
Combined water	4,5 - 6 %
Purity index	75 - 80 %
Grind thinness (sieve 0,2 mm)	<25%
Resistance to flexotraction	2,3 N/mm2
pH	7,8
Reaction to fire	A1
Stockage (from manufacturing date, under cover, in a dry place)	12 months



Composition

- Gypsum
- Additives

Precautions

Product components are not toxic.
It must be worked with gloves, avoid powder inhalation and contact with eyes and skin.
Keep away from children or animals.

First Aid

Skin: Wash with plenty of water
Eyes: Wash with plenty of water
Ingestion: Rinse with water and drink plenty of water

This technical data is written according to our knowledge and essays and doesn't assume any commitment. It's on customer's responsibility the admission and control in the distributor's warehouse or construction, as well as the election of the product to be used on each case. Manufacturer's responsibility is limited to manufacturing defects and for the value of the merchandise because it's out of his control the material election and the working conditions. Technical data for 2018.



Headquarters: Camino Viejo de Simancas, Km. 4 - 47008 Valladolid (Spain) / telf: +34 983 47 52 12
papresa@papresa.net - www.papresa.net

YESO