

YESO DE PROYECTAR ALIGERADO

Gypsum for mechanical application



What is this product

- It's a lightweight construction gypsum for mechanical application and slow forging for indoor wall covering.

Most common uses:

- Indoor wall fast covering.
- Indoor ceiling fast covering.



Characteristics

- Easy mechanical application
- Slow forging
- Minimum retraction after forging
- Monocomponent
- Incorporating perlite aggregate

How to prepare

- 1- Mix the product with a 90% of water. Water quantities might change according to worker's fluidity preferences.
- 2- Coat must be 10-15 mm

Technical Data: Yeso de Proyectar Aligerado

Aspect	White Powder
Presentation	25 kgs bag
Water / gypsum relation	1/1
Forging start	3 hours
Combined water	4 - 6 %
Purity index	75-80%
Grind thinness (sieve 0,2 mm)	<25%
pH	12
Fire Reaction	A1
Stockage (from manufacturing date, under cover, in a dry place)	12 months



Composition

- Gypsum
- Additives

Precautions

Product components are not toxic.
It must be worked with gloves, avoid powder inhalation and contact with eyes and skin.
Keep away from children or animals.

First Aid

Skin: Wash with plenty of water
Eyes: Wash with plenty of water
Ingestion: Rinse with water and drink plenty of water

This technical data is written according to our knowledge and essays and doesn't assume any commitment. It's on customer's responsibility the admission and control in the distributor's warehouse or construction, as well as the election of the product to be used on each case. Manufacturer's responsibility is limited to manufacturing defects and for the value of the merchandise because it's out of his control the material election and the working conditions. Technical data for 2018.

YESO



Headquarters: Camino Viejo de Simancas, Km. 4 - 47008 Valladolid (Spain) / telf: +34 983 47 52 12
papresa@papresa.net - www.papresa.net